

# TRION-ARINC429/MIL1553



## TRION-ARINC429/MIL1553

- ▶ ARINC 429 module with up to 16 channels
- ▶ MIL 1553 module with up to 4 channels



### Module specifications

	TRION-ARINC429	TRION-MIL1553
Input channels	4 channels with 4 shared RX/TX channels 16 channels with 8 shared RX/TX channels and 8 RX channels	1 channel with dual function 4 channels with dual function
Connector	SCSI 3 cable assembly with flying leads 36"	SCSI 3 cable assembly with 1553 3-plug stub cables
Baud rate	12.5 k, 50 k and 100 k	-
Power consumption	4 CH @ 4.5 W 16 CH @ 6.0 W	1 CH @ 5.5 W 4 CH @ 8.5 W
Operating temperature	0 to +70 °C	
Additional features	-	1553A and 1553B support
Parts number <sup>1)</sup>	CPCIC3-A429-4-T CPCIC3-A429-16-T	CPCIC3-1553-1D-T CPCIC3-1553-4D-T
OXYGEN software support	<ul style="list-style-type: none"> <li>▶ Decoding of ARINC 429 / MIL 1553 signals</li> <li>▶ Visualization of binary data</li> <li>▶ Export of decoded signals</li> </ul>	<ul style="list-style-type: none"> <li>▶ Decoding of MIL 1553 signals</li> <li>▶ Visualization of binary data</li> <li>▶ Export of decoded signals</li> <li>▶ Custom message decoder for signal visualization in OXYGEN</li> </ul>
	<ul style="list-style-type: none"> <li>▶ Integrated internal database (equipment IDs and labels from the ARINC standard<sup>2)</sup>)</li> <li>▶ Support of different baud rates for ARINC 429</li> <li>▶ Check of parity bit</li> <li>▶ Settings for equipment IDs and labels</li> </ul>	

Tab. 77: Module specifications

1) For additional hardware specifications refer to the manufacturer's [ARINC429 datasheet](#) or [MIL1553 datasheet](#).

2) ARINC specification 429P1-19 (Digital Information Transfer System Set)